



SAFETY DATA SHEET

ARMOR ALL TIRE FOAM AEROSOL

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME ARMOR ALL TIRE FOAM AEROSOL

SUPPLIER Clorox Car Care,
Unit 16, Rassau Industrial Estate,
Ebbw Vale,
Gwent NP23 5SD, UK
44 (0) 1495 350234
44 (0) 1495 350234

EMERGENCY TELEPHONE 44 (0) 1495 350234

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
DIMETHYL ETHER	204-065-8	115-10-6	1-5%	F+;R12
SODIUM NITRITE	231-555-9	7632-00-0	< 1%	O;R8 T;R25 N;R50

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Extremely flammable.

CLASSIFICATION F+;R12.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues.

INGESTION

Due to the physical nature of this product swallowing is not likely to occur. However, if the product is swallowed Rinse mouth thoroughly. Get medical attention. Provide rest, warmth and fresh air.

SKIN CONTACT

Wash the skin immediately with soap and water. Do not use solvents or thinners.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Carbon dioxide (CO₂). Dry chemicals, sand, dolomite etc. Foam.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out.

UNUSUAL FIRE & EXPLOSION HAZARDS

Extremely flammable. Aerosol cans may explode in a fire.

SPECIFIC HAZARDS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ARMOR ALL TIRE FOAM AEROSOL**SPILL CLEAN UP METHODS**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Once the propellant has completely vented, absorb any remaining liquid in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE**STORAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
DIMETHYL ETHER	WEL	400 ppm	766 mg/m3	500 ppm	958 mg/m3

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid Aerosol		
COLOUR	White Milky.		
RELATIVE DENSITY	1.009 - 1.017 @ 25 °C	pH-VALUE, CONC. SOLUTION	8.5 - 10.0

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION**INHALATION**

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system or lungs. Drowsiness, dizziness, disorientation, vertigo. Central nervous system depression.

SKIN CONTACT

Prolonged contact may cause irritation.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk).

14 TRANSPORT INFORMATION

ARMOR ALL TIRE FOAM AEROSOL



PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	ADR CLASS NO.	2
ADR CLASS	Class 2: Gases	ADR LABEL NO.	2.1
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2
UN NO. SEA	1950	IMDG CLASS	2
EMS	2-13	MFAG	See Guide
UN NO. AIR	1950	AIR CLASS	2

15 REGULATORY INFORMATION

LABELLING



Extremely Flammable

RISK PHRASES

R12 Extremely flammable.

SAFETY PHRASES

- S2 Keep out of the reach of children
- S16 Keep away from sources of ignition - No smoking.
- S25 Avoid contact with eyes.
- S51 Use only in well-ventilated areas.
- A1 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
- A2 Do not spray on a naked flame or any incandescent material.

DETERGENT LABELLING

- 5-15% Aliphatic hydrocarbons
- < 5% Non-ionic surfactants
- Contains SODIUM BENZOATE,2,6-DIMETHYL-1,3-DIOXAN-4-YL ACETATE

NATIONAL REGULATIONS

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

16 OTHER INFORMATION

REVISION COMMENTS

Compliant with CHIP 3.1 (29th ATP). Workplace Exposure Limits (WEL) now replace Occupational Exposure Standards (OES) and Maximum Exposure Limites (MEL). Detergent labelling information now included in Section 15. Amendments to Sections: 2, 8, 15, 16.

REVISION DATE 10-2005

REV. NO./REPL. SDS GENERATED 2 / 01-2003

RISK PHRASES IN FULL

- R12 Extremely flammable.
- R25 Toxic if swallowed.
- R50 Very toxic to aquatic organisms.
- R8 Contact with combustible material may cause fire.

ARMOR ALL TIRE FOAM AEROSOL

DISCLAIMER

The information supplied here is accurate to the best knowledge and belief of Clorox Car Care, it is however, not intended as a warranty or representation, and should not be construed as such, for which Clorox Car Care assumes any legal responsibility. Any information or advice obtained from Clorox Car Care other than by means of this publication, and whether relating to Clorox Car Care's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Clorox Car Care when used instead of, or in conjunction with materials supplied by Clorox Car Care, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Clorox Car Care accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.